


MD-226 Series

26-inch wide-screen marine display



Features and Benefits

- 26-inch full-HD display, 16:10 aspect ratio
- High quality LCD with LED backlight
- Color calibrated for ECDIS compliance (available by CTOS)
- Full range dimming, 0 to 100%
- SavvyTouch display controls
- Built-in RS-232/422/485 interfaces
- Dual power supplies (AC & DC)
- IP54 (front)/IP22 (rear) rated

Certifications



Introduction


The MD-226 Series of marine displays comes with full range dimming, wide viewing angles, and optional optical bonding. These displays are built with a small-profile modular design that allows easier integration into industrial marine systems, reducing deployment costs and overall time-to-market.

The innovative and user-friendly SavvyTouch display controls offer several unique features not found on any other marine display console: a proximity sensor for convenient adjustments in dark conditions, an info button for immediate updates on hardware status, and a quick-switch to adjust between day, dusk, and night-time ECDIS modes (for color-calibrated ECDIS models only).

The MD-226 Series displays are compliant with IEC 60945, DNV, and IACS-E10, verifying their resilience and durability in maritime conditions. Their IP54-rated enclosure provides additional protection against dust and moisture above and beyond the limits established by these international standards bodies.

ECDIS-approved models are also available, offering an excellent HMI solution for ECDIS charting and navigation stations.

Appearance



Specifications

Computer Interface

Serial Ports	RS-232 ports x 1 (DB9 male) RS-232/422/485 ports x 1, software-selectable (terminal block)
Video Input	DVI-D x 1, 29-pin DVI-D connectors (female) VGA x 1, 15-pin D-sub connector (female)

Display

Active Display Area	550.08 (H) x 343.8 (V) mm
Aspect Ratio	16:10
Contrast Ratio	1500:1
Light Intensity (Brightness)	300 cd/m ²
Max. No. of Colors	16.7M (8-bit/color)
Panel Size	26-inch viewable image
Panel Type	MVA
Pixel Pitch (RGB)	0.2865 (H) x 0.2865 (V) mm
Pixels	1920 x 1200
Response Time	15 ms (gray to gray)
Viewing Angles	176°/176°

Serial Interface

Baudrate	50 bps to 115.2 kbps
Data Bits	5, 6, 7, 8
Flow Control	RTS/CTS, XON/XOFF, ADDC® (automatic data direction control) for RS-485, RTS Toggle (RS-232 only)
Parity	None, Even, Odd, Space, Mark
Stop Bits	1, 1.5, 2

Serial Signals

RS-232	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
RS-422	Tx+, Tx-, Rx+, Rx-, GND
RS-485-2w	Data+, Data-, GND
RS-485-4w	Tx+, Tx-, Rx+, Rx-, GND

Power Parameters

Input Voltage	100 to 240 VAC, 24 VDC (18 to 30 V)
---------------	-------------------------------------


Physical Characteristics

Housing	Metal
IP Rating	IP54, front IP20, rear
Dimensions	621 x 444 x 90 mm (24.45 x 17.48 x 3.57 in)

Weight	12,650 g (27.89 lb)
Installation	Desktop, Panel mounting, VESA mounting
Environmental Limits	
Operating Temperature	-15 to 55°C (5 to 131°F)
Storage Temperature (package included)	-20 to 60°C (-4 to 140°F)
Ambient Relative Humidity	5 to 95% (non-condensing)
Standards and Certifications	
EMC	EN 55032/24
EMI	CISPR 32, FCC Part 15B Class A
EMS	IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV IEC 61000-4-6 CS: 10 V
Maritime	ABS, CCS, DNV-GL, IEC 60945
Safety	UL 60950-1
Warranty	
Warranty Period	LCD: 1 year System: 3 years
Details	See www.moxa.com/warranty
Package Contents	
Device	1 x MD-226 Series display
Cable	1 x DVI-D cable 1 x VGA
Installation Kit	1 x terminal block, 2-pin 1 x terminal block, 5-pin
Documentation	1 x document and software CD 1 x quick installation guide 1 x warranty card

Dimensions

Unit: mm (inch)



Ordering Information

Model Name	Panel	Video Inputs	Touchscreen	Power Input	IP Rating	Operating Temp.
MD-226X	26" (16:10) 300 nits	1 x VGA 1 x DVI-D	-	24 VDC (18-30 V) 100-240 VAC	IP54 (front), IP20 (rear)	-15 to 55°C

Accessories (sold separately)

Desktop Mounting Kits

MPC-MD-2-24-26-DMTK w/ hinge	Desktop-mounting kit for 24/26-inch panels
MPC-MD-2-24-26-DMTK w/o hinge	Desktop-mounting kit for 24/26-inch panels, (no hinge)

VESA Mounting Kits

MPC-MD-2-26-VESAMTK	VESA kit for 26-inch panels (can be used with 200 x 100 mm or 280 x 150 mm VESA mounts)
---------------------	---

© Moxa Inc. All rights reserved. Updated Apr 15, 2019.

This document and any portion thereof may not be reproduced or used in any manner whatsoever without the express written permission of Moxa Inc. Product specifications subject to change without notice. Visit our website for the most up-to-date product information.