ioPAC 8600 Series (86M) Modules

Rugged modules for the ioPAC 8600 Series

Features and Benefits

- Complies with all EN 50155 mandatory test items[1]
- Complies with EN 50121-4
- Rugged and compact design for harsh environments
- Expand the I/O and communication capabilities of your ioPAC 8600 Series device
- Wide operating temperature range: -40 to 75°C (-40 to 167°F)
- Channel-to-channel isolated digital input and output
- 24 to 110 V DI/O module and universal power input range module
- Supports CAN bus for CAN 2.0 A/B communication

Certifications

EN 50155 EN 50121-4 CE FC

Introduction

Moxa's ioPAC 8600 Series 86M Modules include channel-to-channel isolated DIs, channel-to-channel isolated DOs, relays, and AOs to provide even more I/O options for ioPAC 8600 Series devices. Combined with the 85M modules, users have a wide variety of options to choose from, allowing them to select the I/O combination that best fits their target application. All 86M modules are designed for railway industry applications, and as such, are compliant with EN 50121-3-2, EN 50121-4, and all EN 50155 mandatory test items. In addition, these modules all support a wide operating temperature range of -40 to 75°C for reliable operation even in harsh environments.

Specifications

Input/Output Interface	
Analog Output Channels	86M-4420-T: 4
Digital Input Channels	86M-1620D-T: 16 86M-1832D-T: 8
Digital Output Channels	86M-2830D-T: 8
Relay Channels	86M-2604D-T: 6
Isolation	3k VDC or 2k Vrms
2-Wire Ethernet Ports	86M-5212U-T: 2
CAN Ports	86M-5212U-T: 2 86M-5250-T: 2

Digital Inputs	
Voltage	86M-1620D-T: 24 to 110 VDC 86M-1832D-T: 24 VDC
Channel-to-Channel Isolation	86M-1832D-T: 1k VDC
Connector	Spring-type Euroblock terminal

1. This product is suitable for rolling stock railway applications, as defined by the EN 50155 standard. For a more detailed statement, click here: www.moxa.com/doc/specs/EN_50155_Compliance.pdf

Counter Frequency	86M-1832D-T: 5k Hz
Debouncing Function	86M-1620D-T: Software enable/disable
Debouncing Time	86M-1620D-T: 1 to 15 ms (software-selectable)
Digital Filtering Time Interval	86M-1832D-T: Software configurable
I/O Mode	86M-1620D-T: DI 86M-1832D-T: DI, event counter, or frequency
Points per COM	86M-1620D-T: 8 channels
Scan on Time	86M-1620D-T: 0.5 ms
Scan Period	86M-1620D-T: 8 ms (typical)
Sensor Type	86M-1620D-T: PNP 86M-1832D-T: Wet Contact (NPN or PNP)
Wet Contact (DI to COM)	86M-1832D-T: On: 10 to 30 VDC 86M-1832D-T: Off: 0 to 3 VDC 86M-1620D-T: On: > 0.3 times external power voltage 86M-1620D-T: Off: < 0.15 times external power voltage

Digital Outputs

Voltage	24 VDC
Connector	Spring-type Euroblock terminal
Current Rating	200 mA per channel
I/O Mode	DO or PWM
I/O Type	Sink
Over-Temperature Shutdown	175°C (typical), 150°C (min.)
Over-Voltage Protection	41 VDC
Pulse Output Frequency	1 kHz
Short-Circuit Protection	750 mA @ 25°C

Relays

Connector	Spring-type Euroblock terminal
Contact Current Rating	Resistive load: 5 A @ 30 VDC, 250 VAC
Contact Resistance	100 milli-ohms (max.)
Electrical Endurance	60,000 operations @ 5 A resistive load
I/O Mode	Relay or PWM
Initial Insulation Resistance	1,000 mega-ohms (min.) @ 500 VDC
Mechanical Endurance	5,000,000 operations
Pulse Output Frequency	0.33 Hz at rated load
Type	Form A (N.O.) power relay

Analog Outputs

Accuracy	±0.1% FSR @ 25°C ±0.3% FSR @ -40 to 75°C
Connector	Spring-type Euroblock terminal
Current Load Resistance	External 24 VDC power: 1000 ohms Internal power: 400 ohms
I/O Mode	Static or waveform mode
Output Range	0 to 10 VDC 0 to 20 mA -10 to 10 V 4 to 20 mA
Resolution	12-bit
Voltage Output	10 mA (max.)
Waveform Frequency	125 Hz
Waveform Type	Sine, Square, Triangle

Ethernet Interface

Connector	M12 D-coded 2-pin female connector
No. of Ports	2
Standards	BroadR-Reach® for 10 Mbps and 100 Mbps IEEE 802.3 for 10BaseT IEEE 802.3u for 100BaseT(X) and 100BaseFX

CAN Interface

Industrial Protocols	CAN 2.0A, CAN 2.0B, CANopen DS301, V4.02
Baudrate	10/20/50/125/250/500/800/1000 kbps, user-defined
Connector	DB9 male
Isolation	3k VDC or 2k Vrms
No. of Ports	2
Terminator	N/A, 120 ohms (by DIP)

Power Parameters

Power Consumption	86M-1620D-T: 12.6 mA @ 24 VDC 86M-1832D-T: 12.6 mA @ 24 VDC 86M-2604D-T: 127 mA @ 24 VDC 86M-2830D-T: 76.7 mA @ 24 VDC 86M-4420-T: 143.8 mA @ 24 VDC 86M-5212U-T: 79.2 mA @ 24 VDC 86M-5250-T: 60.0 mA @ 24 VDC

Physical Characteristics

Dimensions	25 x 128.2 x 85.5 mm (0.98 x 5.05 x 3.37 in)
Weight	Under 80 g
Wiring	I/O cable, 14 to 28 AWG

Environmental Limits

Operating Temperature	-40 to 75°C (-40 to 167°F)
Storage Temperature (package included)	-40 to 85°C (-40 to 185°F)
Ambient Relative Humidity	5 to 95% (non-condensing)
Altitude	2000 m[2]

Standards and Certifications

EMC	EN 55032/24, EN 61000-6-2/-6-4
EMI	CISPR 32, FCC Part 15B Class A
EMS	IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 5100 MHz to 6000 MHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFMF
Railway	EN 50121-4, EN 50155
Safety	UL 508
Shock	IEC 60068-2-27
Vibration	IEC 60068-2-6

MTBF

Time	86M-1620D-T: 1,115,244 hrs 86M-1832D-T: 1,149,108 hrs 86M-2604D-T: 4,173,843 hrs 86M-2830D-T: 1,766,037 hrs 86M-4420-T: 2,409,345 hrs 86M-5212U-T: 2,498,942 hrs 86M-5250-T: 3,306,609 hrs
Standards	Telcordia SR332

Warranty

Warranty Period	5 years
Details	See www.moxa.com/warranty

Package Contents

Device	1 x ioPAC 8600 Series (86M) module
Documentation	1 x warranty card

Ordering Information

Model Name	Input/Output Interface	Input/Output Mode	Type	Channel LED
86M-1620D-T	16 x DI	24-110 VDC	Sink	✓
86M-1832D-T	8 x DI	24 VDC ch-to-ch isolation	Sink/source	✓
86M-2604D-T	6 x Relay	Form A (N.O.)	–	✓
86M-2830D-T	8 x DO	24 VDC ch-to-ch isolation	Sink	✓
86M-4420-T	4 x AO	±10 V 0-10 V	–	–

2. Please contact Moxa if you require products guaranteed to function properly at higher altitudes.

Model Name	Input/Output Interface	Input/Output Mode	Type	Channel LED
		0-20 mA 4-20 mA		
86M-5212U-T	2 x 2-wire Ethernet	100BASE-TX IEEE 802.3u 10BASE-T IEEE 802.3 100 Mbps BroadR-Reach 10 Mbps BroadR-Reach	–	✓
86M-5250-T	2 x CAN	CAN 2.0A CAN 2.0B CANopen DS301, V4.02	–	✓

© Moxa Inc. All rights reserved. Updated Nov 12, 2018.

This document and any portion thereof may not be reproduced or used in any manner whatsoever without the express written permission of Moxa Inc. Product specifications subject to change without notice. Visit our website for the most up-to-date product information.